


JOOSTE

Suier & Pomp Mpy. (Edms) Bpk
Cylinder & Pump Co. (Pty) Ltd



Delivery Table for Jooste Cylinders driven by Windmills or Powerheads

THE LITRES PER HOUR ARE AN INDICATION ONLY.

CYLINDER MODEL	CYLINDER DIAMETER		TOTAL HEAD (METERS)	ROD SIZE (MM)	MINIMUM WINDMILL WHEEL (FOOT)	LITRES (PER HOUR)
	MM	INCH				
AS50	49.2	2	60	12	8	500
AS50RDS	49.2	2	100	16	10	494
AS50RDS	49.2	2	150	16	14	489
AS50RDS	49.2	2	240	16	16	480
AS60	61.2	2.5	50	16	8	770
AS60	61.2	2.5	60	16	10	769
AS60RDS	61.2	2.5	80	16	10	767
AS60RDS	61.2	2.5	100	16	12	765
AS60RDS	61.2	2.5	80	16	14	760
AS70	73.2	3	40	16	8	1,100
AS70	73.2	3	60	16	10	1,098
AS70RDS	73.2	3	80	16	12	1,096
AS70RDS	73.2	3	120	16	16	1,092
AS70RDS	73.2	3	130	16	16	1,091
AS80	81.5	3.5	30	16	8	1,370
AS80	81.5	3.5	50	16	10	1,368
AS80	81.5	3.5	60	16	12	1,367
AS80RDS	81.5	3.5	70	16	12	1,366
AS80RDS	81.5	3.5	100	16	14	1,363
AS80RDS	81.5	3.5	120	16	16	1,361
AS100	100	4	20	16	8	2,100
AS100	100	4	40	16	12	2,098
AS100	100	4	50	16	12	2,097
AS100	100	4	60	16	14	2,096
AS130	125	5	20	16	10	3,250
AS130	125	5	30	16	12	3,249
AS130	125	5	50	16	14	3,247
AS130	125	5	60	16	16	3,246
AS150	152.4	6	20	16	12	4,700
AS150	152.4	6	30	16	14	4,699
AS150	152.4	6	40	16	16	4,698
AS180	177.8	7	20	20	14	6,500
AS180	177.8	7	30	20	16	6,499